

Flange output shaft (similar ISO 9409-1)


Materials / Surfaces:


- Input flange: Aluminum / untreated
- Housing: Steel / heat-treated and post-oxidized (black)
- Output flange: Steel / untreated

Hints:

Please pay attention to the operating and mounting instructions.
Subject to modifications.

Variables on the drawing are dependent upon the motor.
The given dimensions are exemplary



	Scale: 7:10	DIN A3	ISO
	Revision status: Q from: 05/2022		
	Changed revision status: P from: 01/2021		
General tolerance DIN ISO 2768-cL	PLFN090-aii-SSSD3AE-Z(D20) /(L20)/(D21)/(D22)/B5/(G3)		
Neugart GmbH Keltenstr. 16 D-77971 Kippenheim			Sheet 1/2

General gearbox data	Character	Unit	
Planetary gearbox - gearing type	-	-	Straight teeth
Rotation direction	-	-	Input and output in the same direction
Number of stages	p	-	1-stage
Output shaft bearing	-	-	Inclined roller bearings
Service life (L10h)	t_L	h	20.000
Max. operating temperature	T_{min} / T_{max}	°C	-25 / +90
Protection class	-	-	IP 65
Lubrication (Lifetime lubrication)	-	-	Standard lubrication (Castrol Optigear Synthetic 800/150)
Installation position	-	-	Any
Max. bending moment based on the gearbox input flange (for motor weight) (1)	M_b	Nm	38
Motor shaft concentricity / Coaxiality and axial runout Motor flange	-	mm	0,015 / 0,03 (Measuring methods according to DIN EN 50347)
Required motor shaft tolerance	-	-	j6; k6
Min. permissible motor shaft length	$L_{20 min}$	mm	19
Reference operating mode	-	-	S1
Reference operating factor	K_A	-	1
Reference speed	n_2	rpm	100
Reference ambient temperature	T_{Amb}	°C	20
Radial force for output bearing based on shaft end after L10h=20,000h with Fa=0N	$F_r 20.000h$	N	3950
Axial force for output bearing based on gearbox axis after L10h=20,000h with Fr=0N	$F_a 20.000h$	N	8200
Radial force for output bearing based on shaft end after L10h=30,000h with Fa=0N	$F_r 30.000h$	N	3500
Axial force for output bearing based on gearbox axis after L10h=30,000h with Fr=0N	$F_a 30.000h$	N	7200
Maximum radial force based on shaft end and T2=0Nm	$F_r Max$	N	3950
Maximum axial force based on gearbox axis and T2=0Nm	$F_a Max$	N	8200

$$(1) \text{ Max. motor weight* in kg} = \frac{0,2 \times M_b}{\text{motor length in m}}$$

- * with symmetrically distributed motor weight
- * with horizontal and stationary mounting

Ratio-dependent gearbox data	Character	Unit					
Ratio	aii	-	4	5	7	8	10
Nominal output torque	T_{2N}	Nm	140	140	90	80	60
Max. output torque for 30.000 output shaft rotations	T_{2max}	Nm	224	224	144	128	96
Emergency stop torque permitted 1000 times	T_{2stop}	Nm	280	280	175	200	200
Average idle torque for $n_1=3,000$ rpm and 20 °C gearbox temperature	T_0	Nm	1,55	1,15	0,75	0,65	0,55
Average thermal input speed at 50% T2N, S1, and T_Amb Operating temperature may not be exceeded!	$n_{1N 50\%}$	rpm	1750	2100	3000	3350	4000
Average thermal input speed at 100% T2N, S1, and T_Amb Operating temperature may not be exceeded!	$n_{1N 100\%}$	rpm	1350	1650	2500	2850	3600
Max. mechanical input speed Operating temperature may not be exceeded!	$n_{1 Limit}$	rpm	10000	10000	10000	10000	10000
Torsional backlash based on output shaft	j_t	arcmin	< 3	< 3	< 3	< 3	< 3
Torsional stiffness based on output shaft	c_g	Nm/arcmin	35	40,5	27	27	22
Efficiency at T2N, gearbox temperature 70 °C and $n_1=1,000$ rpm	η	%	97	97	96	96	95
Running noise at $n_1=3,000$ rpm without load at a distance of 1m	Q_g	dB(A)	62	62	62	62	62
Gearbox weight	m_G	kg	2,9	3	3	3	3
Mass moment of inertia based on clamping system diameter input	J	kgcm ²	0,92	0,753	0,639	0,613	0,58

Subject to modifications.



PLFN090-aii-SSSD3AE-Z(D20)
/(L20)/(D21)/(D22)/B5/(G3)

Sheet 2/2

Revision status: Q from: 05/2022